

เอกสารข้อมูลผลิตภัณฑ์

ข้อมูลจำเพาะ

APC



APC Easy UPS On-Line,
3kVA/2400W, Tower, 230V, 6x IEC
C13 + 1x IEC C19 outlets, Intelligent
Card Slot, LCD, Extended runtime

SRV3KIL

Overview

Presentation High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.

Lead time Usually in Stock

Main

Main Input Voltage 230 V

Other Input Voltage 220 V
240 V

Main Output Voltage 230 V

Other Output Voltage 220 V
240 V

Rated power in W 2400 W

Rated power in VA 3000 VA

Input Connection Type IEC 60320 C20

Output connection type 6 IEC 60320 C13
1 IEC 60320 C19

Cable length 1.52 m

Number of cables 1

Provided equipment 1 IEC 60320 C19 to Schuko power cable
1 IEC 60320 C13 to C14 power cable
1 USB cable
1 RS-232 configuration cable
1 external battery pack
1 battery cable
user manual

General

Number of power module filled slots 0

Number of power module free slots 0

Redundant No

Physical

Colour Black (RAL 7010)

Height 33.6 cm

Width	42.5 cm
Depth	42.5 cm
Net weight	45.9 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Not rack-mountable
USB compatible	Yes
Mounting position	Vertical

Input

Input voltage limits	110...285 V half load 160...280 V full load
Network frequency	40...70 Hz auto sensing

Output

Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2400 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Harmonic distortion	3 %
Transfer time	4 ms typical
UPS type	Double conversion online
Wave type	Sine wave
Efficiency	88 % (full load)
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1

Conformance

Product certifications	CE UKCA EAC TISI
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-20...50 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...15000 m
Acoustic level	50 dBA
Heat dissipation	910 Btu/h

IP degree of protection	IP20
-------------------------	------

Batteries & Runtime

Battery type	Lead-acid battery
--------------	-------------------

Battery voltage	72 V
-----------------	------

Number of battery filled slots	0
--------------------------------	---

Number of battery free slots	0
------------------------------	---

Battery recharge time	5.5 h
-----------------------	-------

Battery life	3...5 year(s)
--------------	---------------

Battery charger power	350 W rated
-----------------------	-------------

Battery option	SRV72BP-9A 1 1878 VAh SRV72BP-9A 2 2817 VAh SRV72BP-9A 3 3756 VAh SRV72BP-9A 4 4695 VAh
----------------	--

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
-------	--

Free slots	1
------------	---

Control panel	Multifunction LCD status and control console
---------------	--

Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	2
------------------------------	---

Package 1 Height	46.5 cm
------------------	---------

Package 1 Width	56.5 cm
-----------------	---------

Package 1 Length	56.5 cm
------------------	---------

Package 1 Weight	49.8 kg
------------------	---------

Offer Sustainability

REACH Regulation	REACH Declaration
------------------	-----------------------------------

EU RoHS Directive	Compliant EU RoHS Declaration
-------------------	--

Mercury free	Yes
--------------	-----

China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
-----------------------	---

RoHS exemption information	Yes
----------------------------	---------------------

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

ผลิตภัณฑ์ทดแทนที่แนะนำ